



# Jinan Guotai Bearing Co., Ltd



2.362 Inch | 60 Millimeter x 4.331 Inch | 110  
 Millimeter x 1.102 Inch | 28 Millimeter SKF 22212  
 EK/C3 Spherical Roller Bearings

Bearing No. 22212 EK/C3

22212 EK/C3 Bearing 2D drawings and 3D CAD models

Category	Spherical Roller Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	1.141
EAN	7316576652219
Product Group	B04311
Internal Clearance	C3-Loose
Mounting Method	Adapter Mount
Rolling Element	Spherical Roller Bearing
Bore Profile	Tapered
Cage Material	Steel
Enclosure	Open
Number of Rows of Rollers	Double Row
Relubricatable	Yes
Withdrawal Sleeve	AHX312 (Specify bore)
Withdrawal Nut	KM14
Inch - Metric	Metric
Long Description	60MM Tapered Bore; 110MM Outside Diameter; 28MM Width; C3-Loose Clearance; Adapter Mount; Double Row of Spherical Roller Bearings; Steel Cage Material; Open Enclosure; Relubricatable; Adapter Part Num



## Jinan Guotai Bearing Co., Ltd

Other Features	Order adapter or withdrawal sleeve or nut separately. Others may be available
Category	Spherical Roller Bearing
UNSPSC	31171510
Harmonized Tariff Code	84823080
Noun	Bearing
Keyword String	Spherical
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Weight / LBS	2.513
d	2.362 Inch   60 Millimeter
D	4.331 Inch   110 Millimeter
Adapter Part Number	SNW12 H312 HA312 HE312 HS312 (Specify Bore) Inch   H312 (Specify bore) Millimeter
B	1.102 Inch   28 Millimeter
bore diameter:	60 mm
maximum rpm:	7500 RPM
outside diameter:	110 mm
operating temperature range:	Maximum of +390 ° F
overall width:	28 mm
cage material:	Steel
bore type:	Tapered 1:12
bearing material:	Steel
outer ring type:	Not Split
cage type:	Inner Ring Guided
internal clearance:	C3
precision rating:	Not Rated
closure type:	Open
finish/coating:	Uncoated
lubrication hole type:	Lubrication Groove & Hole



## Jinan Guotai Bearing Co., Ltd

outer ring width:	28 mm
dynamic load capacity:	156 kN
fillet radius:	1.5 mm
static load capacity:	166 kN
series:	222