



Jinan Guotai Bearing Co., Ltd



NU 248 MA/C3 Bearing 2D drawings and 3D CAD models

9.449 Inch | 240 Millimeter x 17.323 Inch | 440 Millimeter x 2.835 Inch | 72 Millimeter SKF NU 248 MA/C3 Cylindrical Roller Bearings

Bearing No. NU 248 MA/C3

Category	Cylindrical Roller Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	60.724
EAN	7316577295835
Product Group	B04144
Bore Profile	Straight
Cage Material	Brass
Precision Class	RBEC 1 ISO P0
Number of Rows of Rollers	Single Row
Separable	Inner Ring - Both Sides
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C3-Loose
Retainer	Yes
Relubricatable	Yes
Inch - Metric	Metric
Other Features	Plain Inner Ring 2 Rib Outer Ring Cage on Outer Ring ID
Long Description	240MM Bore; Straight Bore Profile; 440MM Outside Diameter; 72MM Width;



Jinan Guotai Bearing Co., Ltd

	Brass Cage Material; RBEC 1 ISO P0; Single Row; Inner Ring - Both Sides Separable; No Snap Ring; Relubricatable; C3-Loose Inte
Category	Cylindrical Roller Bearing
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	NU 248 MA/C3
Weight / LBS	133.754
d	9.449 Inch 240 Millimeter
D	17.323 Inch 440 Millimeter
B	2.835 Inch 72 Millimeter
bore diameter:	240 mm
static load capacity:	1370 kN
outside diameter:	440 mm
precision rating:	Not Rated
overall width:	72 mm
maximum rpm:	2200 RPM
flanges:	(2) Outer Ring
cage material:	Brass
bore type:	Straight
finish/coating:	Uncoated
number of rows:	1
closure type:	Open
internal clearance:	C3
outer ring width:	72 mm
ring separation:	Separable Ring
fillet radius:	3 mm
operating temperature range:	Maximum of +300 ° F



Jinan Guotai Bearing Co., Ltd

series:	NU2
dynamic load capacity:	952 kN